

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Capalac PU-Härter

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Polyurethane-resin-based coating material, solvent-containing  
stance/Mixture

Recommended restrictions : within adequate application - none  
on use

### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

E-mail address Responsible/issuing person : msds@dr-rmi.com

### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single ex-	H335: May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

posure, Category 3, Respiratory system

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

### 2.2 Label elements

#### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

:

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapours/ spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P405 Store locked up.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

### Hazardous ingredients which must be listed on the label:

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers  
n-butyl acetate  
xylene  
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Polyisocyanate, solvent-containing

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers	53880-05-0 500-125-5 01-2119488734-24	Skin Sens. 1; H317 STOT SE 3; H335 (No specific target organs noted)	>= 50 - < 70
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 20 - < 30
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 10 - < 20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

		STOT SE 3; H335 Asp. Tox. 1; H304 STOT RE 2; H373 Aquatic Chronic 3; H412	
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Flam. Liq. 2; H225	$\geq 2,5 - < 10$
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 615-008-00-5 01-2119490408-31	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 2; H411  specific concentration limit Resp. Sens. 1; H334 $\geq 0,5 \%$ Skin Sens. 1; H317 $\geq 0,5 \%$	$\geq 0,025 - < 0,1$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

General advice : Show this material safety data sheet to the doctor in attendance.  
When symptoms persist or in all cases of doubt seek medical advice.  
Move out of dangerous area.  
First aider needs to protect himself.  
Never give anything by mouth to an unconscious person.

If inhaled : Call a physician.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

Move to fresh air.

- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.  
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
If accidentally swallowed obtain immediate medical attention.  
If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Foam  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : Water

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

### 5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for fire-fighters

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8. Avoid exceeding the given occupational exposure limits (see section 8). Provide sufficient air exchange and/or exhaust in work rooms. Contains isocyanates. Please, attend to producer's advice.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

Liquid product may irritate and sensitize skin and respiratory tract and may cause allergic reaction. Do not inhale vapours. Take care for sufficient fresh air supply during and after use. Product must not be sprayed. Allergics or persons tending to respiratory tract diseases must not be involved in operations with this product.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Keep working clothes separately. Remove and wash contaminated clothing before re-use. Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		AGW	62 ppm	DE TRGS

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version 1.3      Revision Date: 26.01.2023      SDS Number: 6005542      Date of last issue: 17.08.2022  
Date of first issue: 14.11.2019

			300 mg/m <sup>3</sup>	900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	20 ppm 88 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	AGW	0,005 ppm 0,046 mg/m <sup>3</sup>	TRGS 430
	Peak-limit category: 1;=2=(I)			
	Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance			
		AGW (Vapour and aerosols)	0,005 ppm 0,046 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 1;=2=(I)			
	Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Substance sensitizing through the respiratory system			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid	Immediately after	TRGS 903



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version 1.3      Revision Date: 26.01.2023      SDS Number: 6005542      Date of last issue: 17.08.2022  
Date of first issue: 14.11.2019

		(all isomers): 2.000 mg/l (Urine)	exposure or after working hours	
ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	48,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	7,00 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	12,00 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	3,40 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	289,00 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version 1.3      Revision Date: 26.01.2023      SDS Number: 6005542      Date of last issue: 17.08.2022  
Date of first issue: 14.11.2019

	Workers	Inhalation	Acute local effects	289,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
ethylbenzene	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15,00 mg/m3
	Workers	Inhalation	Acute systemic effects	884,00 mg/m3
	Workers	Inhalation	Acute local effects	293,00 mg/m3
	Workers	Inhalation	Acute local effects	884,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	442,00 mg/m3
	Workers	Inhalation	Long-term local effects	442,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Workers	Inhalation	Acute local effects	0,05 mg/m3
	Workers	Inhalation	Long-term local effects	0,05 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Soil	0,0903 mg/kg dry weight (d.w.)
	Sea sediment	0,0981 mg/kg dry weight (d.w.)
	Intermittent use/release	0,36 mg/l
	Sewage treatment plant	35,6 mg/l
xylene	Sea water	0,018 mg/l
	Fresh water	0,18 mg/l
	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Sea water	0,327 mg/l
	Sea sediment	12,46 mg/kg dry

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

		weight (d.w.)
ethylbenzene	Intermittent use/release	0,1 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water	0,1 mg/l
	Sea water	0,01 mg/l
	Fresh water sediment	13,7 mg/kg dry weight (d.w.)
	Soil	2,68 mg/kg dry weight (d.w.)
	Sea sediment	1,37 mg/kg dry weight (d.w.)
	Secondary Poisoning	0,02 g/kg food
	Sea water	0,1 mg/l
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Sea water	0,006 mg/l
	Fresh water	0,06 mg/l
	Sewage treatment plant	10,6 mg/l
	Fresh water sediment	218,92 mg/kg dry weight (d.w.)
	Intermittent use/release	0,04 mg/l
	Soil	44,01 mg/kg dry weight (d.w.)
	Sea sediment	21,89 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

#### Hand protection

Material : butyl-rubber  
Glove thickness : 0,3 mm  
Protective index : Class 3  
Wearing time : 30 min

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes  
Long sleeved clothing  
Remove and wash contaminated clothing before re-use.  
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue:
1.3	26.01.2023	6005542	17.08.2022
			Date of first issue: 14.11.2019

posable suits) to avoid exposed skin surfaces.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : When exceeding the WEL substance Limit a respiratory filter Type A is necessary. Class 1 or 2 has to be chosen depending on the workplace concentration.  
Do not use for spraying.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Color	: No data available
Odor	: No data available
Odor Threshold	: Not relevant
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Flash point	: 30 °C
Autoignition temperature	: not determined
Decomposition temperature	: Not applicable
pH	: 6,95 Concentration: 10 %
Viscosity	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	12 mm <sup>2</sup> /s (40 °C) Method: ISO 3104/3105
Flow time	:	17,0 s Cross section: 4 mm Method: ISO 2431
Solubility(ies) Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	not determined
Relative density	:	not determined
Density	:	1,0100 g/cm <sup>3</sup>
Relative vapor density	:	Heavier than air.

### 9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Not applicable
Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	Not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Amines and alcohols cause exothermic reactions. Mixture reacts slowly with water resulting in evolution of CO <sub>2</sub> .
---------------------	---	---

### 10.4 Conditions to avoid

Conditions to avoid	:	Exposure to water vapor. Protect from frost, heat and sunlight.
---------------------	---	--

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

### 10.5 Incompatible materials

Materials to avoid : Amines  
Incompatible with oxidizing agents.  
Incompatible with acids and bases.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): 14.000 mg/kg

##### **xylene:**

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

##### **ethylbenzene:**

Acute oral toxicity : LD50 Oral (Rat): 3.500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 17.800 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

### 12.3 Bioaccumulative potential

#### Components:

##### **n-butyl acetate:**

Partition coefficient: n-octanol/water	:	log Pow: 2,3 (25 °C) Method: OECD Test Guideline 117
--	---	---

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
------------	---	--

### 12.6 Endocrine disrupting properties

#### Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

### 12.7 Other adverse effects

#### Product:

Additional ecological information	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
-----------------------------------	---	---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	:	Uncured product residues and unpurified packaging should be disposed of as hazardous waste. Waste should not be disposed of via wastewater.  Material residues: Allow the basic substance to harden with hardener and dispose of as paint waste.
Contaminated packaging	:	Only completely emptied containers should be given for recycling.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

Waste Code : used product  
080111\*, waste paint and varnish containing organic solvents  
or other dangerous substances

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

### 14.2 UN proper shipping name

ADN	: PAINT
ADR	: PAINT
RID	: PAINT
IMDG	: PAINT
IATA	: Paint

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

### 14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC  
< 44 %  
< 450 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

### SECTION 16: Other information

#### Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitization
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430	: Germany. TRGS 430 - Isocyanates
TRGS 903	: TRGS 903 - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
DE TRGS 900 / AGW	: Time Weighted Average
TRGS 430 / AGW	: Occupational Exposure Limit

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capalac PU-Härter

Version	Revision Date:	SDS Number:	Date of last issue: 17.08.2022
1.3	26.01.2023	6005542	Date of first issue: 14.11.2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN