

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboFLOOR 475 E.MI PLUS Comp. B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Epoxide-resin-based coating material, totally solid

Recommended restrictions : within adequate application - none
on use

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222

E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1C	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P262 Do not get in eyes, on skin, or on clothing.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P391 Collect spillage.

Hazardous ingredients which must be listed on the label:

Carbomonocyclical, alkylated mixture of Poly-aza-alkanes, hydrated
1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with glycidyl tolyl ether
3-aminopropyldiethylamine
2,2'-iminodiethylamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Carbomonocyclical, alkylated mixture of Poly-aza-alkanes, hydrated	1173092-74-4	Acute Tox. 4; H302 Skin Corr. 1C; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 30 - < 50
1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with glycidyl tolyl ether	84144-79-6 282-199-6 01-2120762088-49	Acute Tox. 4; H302 Skin Corr. 1C; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 30 - < 50
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 1 - < 10
3-aminopropyldiethylamine	104-78-9 203-236-4 612-062-00-1 01-2119965402-39	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 3 - < 5
2,2'-iminodiethylamine	111-40-0 203-865-4 612-058-00-X 01-2119473793-27	Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335	>= 0,1 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- | | |
|-------------------------|--|
| General advice | : Never give anything by mouth to an unconscious person.
If you feel unwell, seek medical advice (show the label where possible).
Move out of dangerous area.
First aider needs to protect himself. |
| If inhaled | : Move to fresh air. |
| In case of skin contact | : Do NOT use solvents or thinners.
In case of contact, immediately flush skin with soap and plenty of water.
Take off all contaminated clothing immediately. |
| In case of eye contact | : IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. |
| If swallowed | : Call a physician.
Clean mouth with water and drink afterwards plenty of water.
If swallowed, DO NOT induce vomiting. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|---|
| Risks | : Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns. |
|-------|---|

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|-----------------------------|
| Treatment | : No information available. |
|-----------|-----------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|------------------------------|--|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Foam
Carbon dioxide (CO ₂) |
|------------------------------|--|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray. Hazardous decomposition products formed under fire conditions.

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.
, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Advice on safe handling : For personal protection see section 8.
Avoid exceeding the given occupational exposure limits (see section 8).
Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against fire and explosion : The product is flammable but not readily ignited.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 8A

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
benzyl alcohol	100-51-6	AGW (Vapour and aerosols)	5 ppm 22 mg/m ³	DE TRGS 900
Peak-limit category: 2;(I)				
Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
benzyl alcohol	Consumers	Skin contact	Acute systemic effects	20,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,00 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version 2.0 Revision Date: 22.02.2023 SDS Number: 6025656 Date of last issue: 27.10.2021
Date of first issue: 27.10.2021

	Consumers	Inhalation	Long-term systemic effects	5,40 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	4,00 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	20,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	27,00 mg/m ³
	Workers	Inhalation	Acute systemic effects	110,00 mg/m ³
	Workers	Inhalation	Long-term systemic effects	22,00 mg/m ³
	Workers	Skin contact	Acute systemic effects	40,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	8,00 mg/kg bw/day
2,2'-iminodiethylamine	Consumers	Skin contact	Long-term systemic effects	4,88 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	27,50 mg/m ³
	Consumers	Skin contact	Acute systemic effects	4,88 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,60 mg/m ³
	Workers	Inhalation	Acute systemic effects	92,10 mg/m ³
	Workers	Inhalation	Acute local effects	2,60 mg/m ³
	Workers	Inhalation	Long-term systemic effects	15,40 mg/m ³
	Workers	Inhalation	Long-term local effects	0,87 mg/m ³
	Workers	Skin contact	Long-term systemic effects	11,40 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	1,10 mg/cm ²

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
benzyl alcohol	Sewage treatment plant	39 mg/l
	Fresh water	1 mg/l
	Sea sediment	0,527 mg/kg dry weight (d.w.)
	Sea water	0,1 mg/l
	Fresh water sediment	5,27 mg/kg dry weight (d.w.)
	Soil	0,456 mg/kg dry weight (d.w.)
	Intermittent use/release	2,3 mg/l
2,2'-iminodiethylamine	Fresh water sediment	1072 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

		weight (d.w.)
	Soil	7,97 mg/kg dry weight (d.w.)
	Sewage treatment plant	6 mg/l
	Fresh water	0,56 mg/l
	Sea sediment	107,2 mg/kg dry weight (d.w.)
	Intermittent use/release	0,32 mg/l
	Sea water	0,056 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection
Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks

: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection

: Safety shoes
Use appropriate degowning techniques to remove potentially contaminated clothing.
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection

: Roller application or brushing: This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Color	: No data available
Odor	: No data available
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Flash point	: > 100 °C
Autoignition temperature	: not determined
Decomposition temperature	: Not applicable
Viscosity	
Viscosity, dynamic	: No data available
Solubility(ies)	
Water solubility	: partly miscible
Partition coefficient: n-octanol/water	: not determined
Vapor pressure	: not determined
Density	: 1 g/cm ³
Relative vapor density	: not determined

9.2 Other information

Oxidizing properties	: Not applicable
Flammability (liquids)	: The product is not flammable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous decomposition products formed under fire conditions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids.
Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 510,62 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

benzyl alcohol:

Acute oral toxicity : LD50 (Rat, male and female): 1.230 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

2,2'-iminodiethylamine:

Acute oral toxicity : LD50 (Rat): 1.080 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0,07 - < 0,3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 1.090 mg/kg

Skin corrosion/irritation

|| Causes severe burns.

Serious eye damage/eye irritation

|| Causes serious eye damage.

Components:

benzyl alcohol:

Species : Rabbit

Assessment : Irritating to eyes.

Respiratory or skin sensitization

Skin sensitization

|| May cause an allergic skin reaction.

Respiratory sensitization

|| Not classified based on available information.

Germ cell mutagenicity

|| Not classified based on available information.

Carcinogenicity

|| Not classified based on available information.

Reproductive toxicity

|| Not classified based on available information.

STOT-single exposure

|| Not classified based on available information.

STOT-repeated exposure

|| Not classified based on available information.

Aspiration toxicity

|| Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | | |
|------------------------|---|---|
| Product | : | Uncured product residues and unpurified packaging should be disposed of as hazardous waste.
Material residues: Allow the basic substance to harden with hardener and dispose of as paint waste.
Waste should not be disposed of via wastewater. |
| Contaminated packaging | : | Only completely emptied containers should be given for recycling. |
| Waste Code | : | used product
080111*, waste paint and varnish containing organic solvents or other dangerous substances |

SECTION 14: Transport information

14.1 UN number or ID number

- | | | |
|------|---|---------|
| ADN | : | UN 2735 |
| ADR | : | UN 2735 |
| RID | : | UN 2735 |
| IMDG | : | UN 2735 |
| IATA | : | UN 2735 |

14.2 UN proper shipping name

- | | | |
|------|---|--|
| ADN | : | AMINES, LIQUID, CORROSIVE, N.O.S.
(Carbomonocyclical, alkylated mixture of Poly-aza-alkanes, hydrated, 1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with glycidyl tolyl ether) |
| ADR | : | AMINES, LIQUID, CORROSIVE, N.O.S.
(Carbomonocyclical, alkylated mixture of Poly-aza-alkanes, hydrated, 1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with glycidyl tolyl ether) |
| RID | : | AMINES, LIQUID, CORROSIVE, N.O.S.
(Carbomonocyclical, alkylated mixture of Poly-aza-alkanes, hydrated, 1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with glycidyl tolyl ether) |
| IMDG | : | AMINES, LIQUID, CORROSIVE, N.O.S.
(Carbomonocyclical, alkylated mixture of Poly-aza-alkanes, hydrated, 1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with glycidyl tolyl ether) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

IATA : Amines, liquid, corrosive, n.o.s.
(Carbomonocyclical, alkylated mixture of Poly-aza-alkanes, hydrated, 1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with glycidyl tolyl ether)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 8	
ADR	: 8	
RID	: 8	
IMDG	: 8	
IATA	: 8	

14.4 Packing group

ADN
Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8

ADR
Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

RID
Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8

IMDG
Packing group : III
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)
Packing instruction (cargo aircraft) : 856
Packing instruction (LQ) : Y841
Packing group : III
Labels : Corrosive

IATA (Passenger)
Packing instruction (passenger aircraft) : 852
Packing instruction (LQ) : Y841

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Packing group : III
Labels : Corrosive

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	: This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: None

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E1 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 3 highly water endangering
Classification according to AwSV, Annex 1 (4)

Product code for laquers and paints / Giscode : RE1 Epoxy resin products, solvent-free, sensitising

. : RE30 Epoxy resin products, sensitising, totally solid

Volatile organic compounds : Directive 2004/42/EC
< 6 %
< 60 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Acute Tox. 4

H302

Classification procedure:

Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

DisboFLOOR 475 E.MI PLUS Comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 27.10.2021
2.0	22.02.2023	6025656	Date of first issue: 27.10.2021

Skin Corr. 1C	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN